# **STAINLESS BALL VALVE** SBV



# **Specification**

- SCREWED BODY CAP
- FULL BORE
- BLOW-OUT PROOF STEM
- PTFE SEAT
- THREADED TO BS 21 (ISO 7) / ASME B1.20.1

#### Material

Part	Material			
Body	Stainless Steel 304			
Ball	Stainless Steel 304			
Seat	PTFE			
Stem	Stainless Steel 304			
Gasket	PTFE			


# **Pressure / Temperature Ratings**

Working Pressure	1.96MPa		
Working Temperature	Max. 120 deg.C		
Suitable Media	Water & Oil		

### Dimensions

Size		L		Н		D	
mm	inch	mm	inch	mm	inch	mm	inch
10	3/8	55	2.2	53	2.1	80	3.1
15	1/2	55	2.2	53	2.1	80	3.1
20	3/4	65	2.6	61	2.4	90	3.5
25	1	76	3.0	67	2.6	90	3.5
32	1 1/4	87	3.4	76	3.0	125	4.9
40	1 1/2	95	3.7	93	3.7	150	5.9
50	2	114	4.5	101	4.1	150	5.9

#### Structure



#### Note:

- 1. If used for gas application, please consult our sales office.
- 2. Design and specifications are subject to change without prior notice.