

## STAINLESS STEEL AUTO AIR VENT

### 不锈钢自动排气阀

#### SPECIFICATION 规格

Threaded to BS 21 (ISO7) / ASME B1.20.1

Size Range: 15mm(1/2")~25mm(1")

螺纹符合BS 21 (ISO7) / ASME B1.20.1

口径范围:15mm(1/2")~25mm(1")

#### PRESSURE/TEMPERATURE RATINGS 压力/温度等级

Working Pressure	工作压力	16bar		
Testing Pressure	测试压力	24bar	Hydrostatic	液压
		5.5bar	Air	气压
Suitable Media	介质	Water 水		

#### MATERIALS 材质表

Part	部件	Material	材质
Body	阀体	Stainless Steel CF8/CF8M	不锈钢CF8/CF8M
Cap	阀帽	Stainless Steel CF8/CF8M	不锈钢CF8/CF8M
Air Cap	气孔帽	Stainless Steel 304/316	不锈钢304/316
Floater	浮球	Polytene	聚乙烯
Floater Bar	浮球杆	Stainless Steel 304/316	不锈钢304/316
Spring	弹簧	Stainless Steel 304/316	不锈钢304/316
O Ring	O型圈	EPDM	三元乙丙
Packing	密封垫	EPDM	三元乙丙

#### DIMENSIONS 口径尺寸

Size	s	H	L
15	1/2"	78	53
20	3/4"	78	53
25	1"	78	53

#### Note:

1. 20A&25A valves will be shipped with adaptor put together with 15A valves.
2. Design and specifications are subject to change without prior notice.

#### 备注:

1. 20A, 25A 口径的产品以 15A 口径的阀配转接器(配套)的方式对应。
2. 设计和规格如有修改,恕不另行通知。

