

STAINLESS STEEL GLOBE VALVE 不锈钢丝扣截止阀

SPECIFICATION 规格

SCREWED-IN BONNET · SWIVEL DISC
RISING STEM · ASBESTOS FREE
THREADED TO BS21(ISO7)/ASME B1.20.1
SIZE RANGE:15mm(1/2")~50mm(2")

阀帽为螺纹接口.阀板能旋转
明杆.无石棉
螺纹符合BS 21(ISO7)/ASME B1.20.1
口径范围:15mm(1/2")~50mm(2")

PRESSURE/TEMPERATURE RATINGS 压力/温度等级

Working Pressure	工作压力	16bar
Testing Pressure	测试压力	Shell(阀体) : 24 bar 液压 Seat(阀座) : 17.6bar 液压 5.5bar 气压
Working Temperature	工作温度	-29 C to 150 C
Suitable Media	介质	Water & Oil 水/油

MATERIALS 材质表

Part	部件	Material	材质
Body	阀体	Stainless Steel CF8/CF8M	不锈钢CF8/CF8M
Bonnet	阀盖	Stainless Steel CF8/CF8M	不锈钢CF8/CF8M
Disc	阀板	Stainless Steel 304/316	不锈钢304/316
Stem	阀杆	Stainless Steel 304/316	不锈钢304/316
Packing	填料	PTFE	特氟龙
Seal ring	密封圈	PTFE	特氟龙
Cap Nut	压盖螺母	Stainless Steel 304	不锈钢304
Handwheel	手轮	Ductile Iron	球墨铸铁

DIMENSIONS 口径尺寸

Size	s	L	H(Open)	W
15	1/2"	67	94.5	70
20	3/4"	79	100	70
25	1"	87	117	80
32	1.1/4"	103	136	80
40	1.1/2"	118	147	100
50	2"	138	170	100

Note:

1. If used for gas application, please consult our sales office.
2. Design and specifications are subject to change without prior notice.

备注:

1. 如应用于气体, 请联系我司确认。
2. 设计和规格如有修改, 恕不另行事先通知。

SGLV
200PSI

