

STAINLESS STEEL FLANGE GATE VALVE**不锈钢法兰闸阀****SPECIFICATION 规格**

RISING STEM · OUTSIDE SCREW AND YOKE
 FLANGED TO JB/T79.1 PN16
 FACE-TO-FACE DIMENSION CONFORMS TO GB/T12224

明杆

法兰规格符合 JB/T79.1 PN16

阀门结构长度符合 GB/T12224

PRESSURE / TEMPERATURE RATINGS 压力/温度等级

Working Pressure 工作压力	16 bar
Testing Pressure 测试压力	Shell (阀体) : 24 bar Seat (阀座) : 17.6 bar
Working Temperature 工作温度	- 29℃~150℃
Suitable Media 介质	Water & Oil 水/ 油

MATERIALS 材质表

Part 部件	Material 材质
Body 阀体	Stainless Steel CF8/CF8M 不锈钢CF8/CF8M
Bonnet 阀盖	Stainless Steel CF8/CF8M 不锈钢CF8/CF8M
Disc 阀板	Stainless Steel 304/316 不锈钢304/316
Stem 阀杆	Stainless Steel 304/316 不锈钢304/316
Stem Support 阀杆支架	Stainless Steel CF8/CF8M 不锈钢CF8/CF8M
Packing 密封	Graphite 石墨
Stem Nut 阀杆螺母	Brass Rod 棒材黄铜
Handwheel 手轮	Ductile Iron 球墨铸铁

DIMENSIONS 口径尺寸

Size [mm]	L [mm]
50	250
65	265
80	280
100	300
125	325
150	350
200	400
250	450
300	500
350	550
400	600
450	650
500	700
600	800

Note:

1. JIS B2239 10K and other flange standards available upon request.
2. Design and specifications are subject to change without prior notice.

备注：

1. 可提供JIS B2239 10K及其他法兰连接标准的产品。
2. 设计和规格如有修改，恕不另行事先通知。

SGV**PN16**

DN50 ~ DN600

